



HSE  
Occupational Health & Safety  
and Environmental Protection unit



# Radiation Protection aspects of the BDF/SHiP prototypes tests in 2018

M. Casolino, C. Ahdida, R. Froeschl, S. Roesler, C. Theis, Y. Pira, Helmut Vincke, Heinz Vincke, P. Vojtyla  
P. Avigni, J. Busom, M. Calviani, J.P. Canhoto Espadanal, H. Dijkstra, J.-L. Grenard, E. van Herwijnen, R. Jacobsson, K. Kershaw, M. Lamont, E. Lopez Sola, T. Ruf, V. Vlachoudis



ARIA19  
23-25 September 2019, South Korea



# Outlook



- BDF/SHiP concept
- SHiP test beams
  - Muon flux measurement
  - Charm production cross section measurement
- BDF prototype target test beam
  - Radiological aspects during the test
  - Benchmark of samples activation and tritium out-diffusion
- Summary and conclusions

# The SPS North Area







# The SPS North Area







# The SPS North Area






# The SPS North Area



# The SHiP experiment


Experimental concept [1]



- **High Intensity** beam into an **heavy target** ( $12\lambda_{\text{int}}$ ):
  - Maximize New Physics particles production
    - either coming from heavy (charmed) meson decays or from proton-nucleus interactions
  - Suppress pion and kaon decays which is source of background
- Minimize the flux of **SM** particles in the detector
- Define a (large) fiducial volume where the **background level** is approximately **zero**
- Detection by decay or by interaction with matter



# SHiP overview




# The Beam Dump Facility at SPS

BDF [2] is a proposed permanent facility in the North Area at CERN

- High intensity proton beam slow extraction → Design of the facility not only driven by radiological constraints
- Proximity to experimental and public areas  
→ **Minimize impact on other facilities and environment**
- Dense target located at the core of the facility
  - Absorb majority of the SPS beam
  - **High activation expected**
- Keep **flexibility for future installations**


## Civil engineering layout and surrounding facilities



### Key beam parameters for SHiP




Momentum	400 GeV/c
Beam intensity on target	$4 \times 10^{13}$
Cycle length	7.2 s
Spill duration	1 s
Avg. beam power on target	355 kW
Protons on target (PoT)/year	$4 \times 10^{19}$
Total PoT in 5 years data taking	$2 \times 10^{20}$





# SHiP muon flux measurement

- SHiP uses a series of **shielding magnets** to **reduce the muon-flux** inside the experiment's acceptance **by several orders of magnitude**
- The design of this shield [3] relies on the phase space of the muons
- Measure the flux and phase space [4] before the construction of the shield







# Shielding requirements

- Proposal to accumulate  $6 \times 10^{11}$  400 GeV/c PoT over a month
  - Need of beam intensity of  $10^7$  p/spill (maximum in normal configuration in this zone is  $10^6$  p/spill)
- Dedicated shielding designed (using FLUKA simulations) to respect ambient dose equivalent rate limits
  - Areas accessible during beam operation classified as Supervised Radiation Area with no permanent workplaces ( $<15 \mu\text{Sv/h}$ ) - This includes the crane driver cabin.

Cross sectional view of target shielding



Prompt ambient dose equivalent rate



Beam parameters for muon flux measurement

Momentum	400 GeV/c
Beam intensity on target per spill	$1 \times 10^7$
Cycle length	14-24 s
Spill duration	4.8 s
Max protons on target (PoT)/week	$2.5 \times 10^{11}$
Total PoT	$6 \times 10^{11}$

CERN Area Classification

Area	Dose limit [year]	Ambient dose equivalent rate		Sign
		permanent	low occupancy	
Non-designated	1 mSv	0.5 $\mu\text{Sv/h}$	2.5 $\mu\text{Sv/h}$	RADIATION
Supervised	6 mSv	3 $\mu\text{Sv/h}$	15 $\mu\text{Sv/h}$	Dosimeter obligatory Dosimètre obligatoire
Simple	20 mSv	10 $\mu\text{Sv/h}$	50 $\mu\text{Sv/h}$	Dosimeter obligatory Dosimètre obligatoire
Limited Stay	20 mSv		2 mSv/h	LIMITED STAY SEJOUR LIMITE Dosimeters obligatory Dosimètres obligatoires
High Radiation	20 mSv		100 mSv/h	HIGH RADIATION HAUTE RADIATION Dosimeters obligatory Dosimètres obligatoires
Prohibited	20 mSv		> 100 mSv/h	PROHIBITED AREA ZONE INTERDITE No Entry Défense d'entrer

Controlled Area

# Radiation measurements and residual activation

- At the beginning of the test beam ambient dose rate were measured
  - Using REM counter (WENDI)
- After 1 week got a request from the experiment to raise intensity to  $2 \cdot 10^7$  p/spill
  - Second measurement was performed to authorized it

Intensity	Measured prompt dose rate (uSv/h)	Simulated prompt dose rate (uSv/h)	Ratio Measured/Simulated
$10^7$ p every 14s	$4 \pm 1$	$4.4 \pm 0.1$	$0.9 \pm 0.2$



# Radiation measurements and residual activation

- At the beginning of the test beam ambient dose rate were measured
  - Using REM counter (WENDI)
- After 1 week got a request from the experiment to raise intensity to  $2 \cdot 10^7$  p/spill
  - Second measurement was performed to authorized it
- After 15 days of cooling residual ambient dose rate from the target were measured



Intensity	Measured prompt dose rate (uSv/h)	Simulated prompt dose rate (uSv/h)	Ratio Measured/Simulated
$10^7$ p every 14s	$4 \pm 1$	$4.4 \pm 0.1$	$0.9 \pm 0.2$
$2 \cdot 10^7$ p every 19s	$7 \pm 1$	$6.5 \pm 0.1$	$1.1 \pm 0.1$

Position	Measured residual dose rate (uSv/h)	Simulated residual dose rate (uSv/h)	Ratio Measured/Simulated
Contact	$11 \pm 1$	$13.0 \pm 0.1$	$0.85 \pm 0.8$
At 10 cm	$4.7 \pm 0.1$	$5.40 \pm 0.02$	$0.87 \pm 0.02$
At 40 cm	$1.0 \pm 0.1$	$1.40 \pm 0.02$	$0.71 \pm 0.07$

Good agreement found with simulations within 30%

# SHiP charm production cross section measurement

- Motivation:
  - Study charm production
  - Measure for first time charm production in hadronic cascades [4]
- Flux of hidden particles and expected tau neutrinos depend on charmed hadron production
- Similar setup as the muon flux measurement



- The target for the muon flux measurement has not been used in this configuration
- Use of dedicated lead target instrumented with nuclear emulsions as tracking detector



# Activation of the target

- No need of additional shielding for the test due to low beam intensity required ( $10^5$  p/spill)
- Particular care of the target:
  - Use of ultra-pure lead slices (up to  $3.5\lambda$ )
  - Keep the activation below Swiss clearance limits (LL)
    - Limit number of pulses on different lead layers



Radionuclide	Half-life	Activity (Bq)	Multiple of LL (Bq/kg)
Pb-202M	3.57h	1.90e+01	0.002
Tl-195	1.16h	1.40e+01	0.001
Pb-199	1.5h	1.00e+01	0.001

Activities of the most activated lead slice after irradiation with 50 spills

- Simulations predicted slices to be well below clearance limits
- Radiation measurements after the test beam confirmed that compliance with the clearance limits for the lead slices and they were therefore treated as non radioactive material

# BDF/SHiP target prototype test

- Target prototype test to evaluate material response and instrumentation in an unprecedented regime of temperature and stresses
- BDF conditions require slow extraction
  - Available in the North Area target zone (TCC2)



- 3 targets in the North Area target zone (T2,T4,T6)
- Intensities up to  $10^{13}$  protons per pulse


Available space for the test beam upstream of T6 thanks to lack of wobbling magnets and absence of vacuum pipe

# BDF/SHiP target prototype test

- The target replica consists in a reduced scale prototype of the BDF final target [5][6]:
  - cylinders have a diameter of 80 mm (instead of 250 mm)
  - same length distribution
  - same core and cladding materials
- High beam load and high density / Z composition of target → high material activation:
  - Target installation and dismantling remote handling friendly
  - Particular care to radiation protection aspects

## Beam parameters for BDF prototype test

Momentum	400 GeV/c
Beam intensity on target	$5 \times 10^{12}$
Cycle length	7.2 s
Spill duration	1 s
Objective protons on target (PoT)	$3 \times 10^{16}$
Power deposited on target each cycle (kW)	23







# Shielding and residual dose rate

- Shielding and residual dose studied with the maximum foreseen intensity and objective PoT ( $3 \cdot 10^{16}$  PoT)
- During the test collected  $2.4 \cdot 10^{16}$  PoT
- Target residual dose rate measured after 11 months and 20 days

Shielding configuration




Residual dose rate for  $3 \cdot 10^{16}$  PoT (1 week cooling)



1<sup>st</sup> beam on 03/10/2018 and 2<sup>nd</sup> on 24/10/2018

Position	Measured dose rate (mSv/h)	Simulated dose rate (mSv/h)
Contact to target	$26 \pm 1$	$25.15 \pm 0.01$
40 cm from target	$5 \pm 1$	$4.42 \pm 0.01$





# Water activation

- Dedicated cooling station for target cooling with demineralized water
  - Risk of target damage due to high mechanical stresses
  - Mechanical filters and ion exchanger to catch impurities and activated ions
- Water activation estimated using Actiwiz3 Creator → 18.7 mSv/h at 40 cm after 1h of beam stop
- PMI at cartridge at 40 cm distance in agreement with simulations

Shielded cooling station



PMI dose rate



# Water activation

- Sampling valve for indication about target integrity → samples included spallation products
  - Debris present in the first 2 samples
  - Fit to simulation indicates bronze as the parent material (target wheels or pins to stop blocks)
  - Chemical analysis scheduled in October 2019 to confirm
  - Quantity estimated 0.03 g/l


## After 1<sup>st</sup> beam session

Nuclide	Activity (Bq/l)	Error 1 sigma
Be-7	7.70E+03	6.6%
Sc<Sc44m	2.49E+01	6.9%
Sc-46	1.51E+01	7.8%
Y-87	1.45E+01	8.4%
Ag-106m	1.41E+01	9.6%

## After 2<sup>nd</sup> beam session

Nuclide	Activity (Bq/l)	Error 1 sigma
Sc<Sc44m	8.69E+01	5.7%
Y-87	4.85E+01	6.2%
Be-7	2.37E+03	6.8%
Sc-46	6.88E+01	6.8%
Lu-171	8.51E+01	6.8%
Tb-155	4.57E+01	7.0%
Tm-166	7.05E+00	7.7%
Yb-169	3.13E+01	7.8%
Gd-149	3.79E+01	8.1%
Eu<Gd146	1.19E+01	8.3%
In-111	1.13E+01	8.5%
Tm-167	7.14E+01	8.9%
Sc-47	1.17E+02	9.2%
Ru-97	1.27E+01	9.3%

NB: Only nuclides with error < 10% are shown





# Tritium out-diffusion

Tritium has a very low radio-toxicity but it can be a radiation hazard when:

- inhaled
- ingested via food or water
- absorbed through the skin
- Tritium is relatively volatile and can diffuse through materials
- 95% of BDF tritium is produced in the target, **out-diffusion** important for the environmental impact of the facility
  - It can be absorbed by the water (HTO form) and circulated in the water cooling system.
- For the iron and concrete shielding tritium outgassing contributes to contamination of air as well during no beam periods.
- Assumption of an immediate **release of 100%** can be **over-conservative**
- In literature **diffusion coefficients** for tritium [7] are **available only for few materials** and not in the full temperature range
  - Arrhenius equation used to extrapolate to operational temperatures



# Tritium out-diffusion from BDF prototype target

## Analysis of tritium concentration in the cooling circuit of the BDF

- Several samples (1 every two months) analysed through liquid scintillation
- Measurements showed higher concentration than simulated

### Two possible explanation of the higher tritium concentration:

- Release of tritium from the bronze debris
- Tritium out-diffusion during beam period → to be estimated

Material	Max temperature during beam (°C)	Temperature no beam (°C)	Ratio between diffusion constants
TZM	280	20	$5 \cdot 10^7$
W	160	20	150
Ta	195	20	10

PoT collected	Simulated H-3 concentration (Bq/l)	Measured H-3 concentration (Bq/l)
2.5e16	$(2.7 \pm 0.3) \cdot 10^5$	$(4.8 \pm 0.5) \cdot 10^5$ (11/2018) $(5.1 \pm 0.5) \cdot 10^5$ (1/2019) $(5.1 \pm 0.5) \cdot 10^5$ (3/2019) $(5.1 \pm 0.5) \cdot 10^5$ (5/2019)

No significant out-diffusion seen during no beam period

# Tritium out-diffusion from BDF samples

- Profit from the BDF prototype test to measure H-3 out-diffusion from different samples
  - Possibility to measure tritium diffusion rates
- Samples include most critical materials for BDF: Tungsten, Tantalum, TZM, Cast Iron and Concrete
- Support for samples on outer target tank and remote handling procedure for sample removal
  - Removed with robot after first irradiation in October 2018 with  $0.9 \cdot 10^{16}$  PoT
- Measure of tritium outgassing in air with a bubbler and outgassing in water by immersing the samples
  - Temperature during the measurement between 12-18 °C

Material sample support



Measurement setup






# Tritium out-diffusion from BDF samples

- Preliminary results shown for a subset of the materials
  - Measurement still ongoing
- Results normalized by the ratio  $\frac{\text{surface}}{\text{volume}}$
- Other beta emitters contamination for the measurement in water shown as shaded area → Tungsten shows the highest contamination
- Higher diffusion from concrete at ambient temperature
  - Good choice to reduce concrete inside BDF He vessel

Material	Simulated H-3 Activity (Bq)
Concrete	$1.6 \cdot 10^5$
Iron	$2.2 \cdot 10^5$
Steel	$8.3 \cdot 10^4$
Tungsten	$8.7 \cdot 10^4$



# Activation of BDF samples to benchmark FLUKA/Activiz simulations

- Profit from the activation of BDF samples to benchmark simulations
- Good agreement between simulation and gamma spectroscopy data
  - From relatively short (few days/weeks after beam stop) to long (few months) cooling times

Concrete





3 weeks of cooling

7 months of cooling

TZM


3 months of cooling

7 months of cooling



# Activation of BDF samples to benchmark FLUKA/Actiwiz simulations

- Profit from the activation of BDF samples to benchmark simulations
- Good agreement between simulation and gamma spectroscopy data
  - From relatively short (few days/weeks after beam stop) to long (few months) cooling times
- Differences between FLUKA and Actiwiz traced down to different low energy neutron cross sections:
  - For example Ca-47 from Ca-46





# Summary and conclusions

- The proposed BDF would be a **new facility** with unprecedented beam intensity deposited on target
  - SHiP will be the first experiment on this facility
- Three test beams have been successfully conducted at CERN during 2018
  - Radiological studies and optimization measures were critical for the success of these test beams
  - Studies of water activation gave insight on the target integrity
  - Profit from the test beams to better understand **tritium out-diffusion**, which it is important for the BDF environmental impact
    - Tritium diffusion measurements on samples **performed at CERN for the first time**
    - **Concrete shows higher diffusion** than other materials
    - Tungsten diffuses out other beta emitters as well
- Part of these studies are included in the BDF comprehensive design study:

*C. Ahdida et al., SPS Beam Dump Facility: Comprehensive Design Study, CERN-PBC-REPORT-2018-001*

# Thank you for your attention!

# References

- [1] **SHiP Collaboration**, *A facility to Search for Hidden Particles (SHiP) at the CERN SPS*, arXiv:1504.04956, 2015
- [2] **K. Kershaw et al.**, *Design Development for the Beam Dump Facility Target Complex at CERN*, JINST 13 P10011, 2018
- [3] **SHiP Collaboration**, *The active muon shield in the SHiP experiment*, JINST 12 P05011, 2017
- [4] **SHiP Collaboration**,  *$\mu$ -flux measurements for SHiP at H4*, CERN-SPSC-2017-020, 2017
- [5] **E. Lopez Sola et al.**, *Beam impact tests of a prototype target for the Beam Dump Facility at CERN: experimental setup and preliminary analysis of the online results*, arXiv:1909.07094, 2019
- [6] **E. Lopez Sola et al.**, *Design of a high power production target for the Beam Dump Facility at CERN*, arXiv:1904.03074, 2019
- [7] **F. Reiter et al.**, *A compilation of tritium-material interaction parameters in fusion reactor materials*, EUR 15217 EN, 1993





[www.cern.ch](http://www.cern.ch)