
Recent Updates at the Black Hills State University Underground Campus (BHUC)

Brianna Mount, Kevin Lesko, Kelsey Oliver-Mallory, Keenan Thomas, Richard Schnee, Eric Miller, Ryan MacLellan, Dongming Mei, Jaret Heise, John Keefner, Markus Horn, Oren Loken, Dave Taylor, Wenqin Xu, Cabot-Ann Christofferson, J.F Wilkerson, Matthew Busch, Reyco Henning

Presented by Alan Poon

May 24, 2017


BHUC Location




BHUC is at 4380 mwe

More on Sanford Lab: Heise, J., J. Phys.: Conf. Ser. 606 (2015).

BHUC Overview



BHUC Cavern: Dec 2014



Construction time lapse: https://vimeo.com/183890905

Surface Coatings



Maas, J.J., Renken, K.J., Int. Radon Symp., 3, 1.1 (1997).



- Shotcrete
- Two coats of Loxon® Masonry Coating Block Surfacer
- One coat of Macropoxy® 646 Fast Cure Epoxy


BHUC Work Area



BHUC Work Area



BHUC Counting Room



Electrical and Network Connections



LN₂ Distribution





Purge Nitrogen Distribution





BHUC Sample Purge System




BHUC Care and Feeding

 BHSU faculty and students are currently underground twice a week for sample changes and any troubleshooting that users may require

BHSU also tracks training required for underground access and provides guides



Detector Queue System



Detectors Underground



Morgan and Maeve




- Operated by Berkeley Low Background Facility
- Pre-screening at LBNL followed by counting underground
- Counting at BHUC since fall 2015

Thomas, K.J., et al., AIP Conf Proc, 1672, 020004 (2015).

Opening Morgan





SOLO



- Previously at Soudan
- Hosted by LZ collaboration (but may be open to more counting in the future)
- Counting at BHUC since April 2016

Attisha, M., et al., AIP Conf. Proc. 785, 75 (2005).


Mordred




- Originally operated by CUBED
- Reconfigured with remote pre-amp
- Currently at BHUC since August 2016


Twins

- Two crystals (one movable) in one lead shield
- Operated by BHSU and BLBF
- Expected by the end of 2017, both crystals currently at SURF




Twins





Ge IV

- Operated by USD and UA
- Initially reserved for nEXO use
- Expected by the end of 2017



MALBEK/MAVRACS

- Operated by Majorana Collaboration
- Previously at KURF
- Currently at SURF
- MALBEK will continue noise and DAQ studies and once finished, will be transformed into a low background counting station (MAVRACS)



Giovanetti, G., et al., Physics Procedia, 61, 77 (2015). Abgrall, N., [The Majorana Collaboration], Adv.High Energy Phys. 365432 (2014).

BetaCage

- Prototype operational at SDSMT
- Neon-gas drift chamber constructed from ultrapure materials.
- The placement of samples inside the chamber, directly under a multiwire proportional counter, provides low threshold, high detection efficiency, and track reconstruction that should greatly reduce backgrounds.
- Sensitivity expected to be 0.1 betas keV⁻¹ m⁻² day⁻¹ and 0.1 alphas m⁻² day⁻¹. (100x better than existing surface screeners)



See Eric Miller's poster and Ahmed, Z., et al., JINST 9, 1009P (2014). Bunker, R., et al., AIP Conf. Proc. **1549**, 132 (2013).


XIA Ultra-low 1800

Operated by LZ Collaboration



Room for more!

...but it's going fast!



Current, planned and nearby low background capabilities

Detector	Detector Type	[U] mBq/kg	[Th] mBq/kg	Owner
Currently at BHUC				
Morgan	2.1 kg p-type, HPGe	0.2	0.2	BLBF
<mark>/Maeve</mark>	1.7 kg p-type, HPGe	0.1	0.1	BLBF
Mordred	1.4 kg n-type, HPGe	0.7	0.7	USD/BLBF
SOLO	0.6 kg, p-type, HPGe	0.6	0.3	LZ
Planned				
Twins	2 x 2.1 kg, p-type, HPGe			BHSU/BLBF
MALBEK/MAVRACS	0.5 kg, p-type, HPGe			MJD
GeIV	p-type, HPGe			nEXO
BetaCage	alpha and beta counter			SDSMT
Alpha Counter	XIA UltraLo 1800			LZ
Nearby				
BHSU ICP-MS	Agilent 7900			BHSU

Limits listed above are average sensitivities for ~1-2 kg sample for 2 weeks sample time

Counting Consortium

- All current and planned counters in the BHUC have agreed to join the counting consortium
- Each counter retains autonomy, but free time on the counter is made available
- Single point of contact for anyone needing analysis

Acknowledgements

- This work was supported by an award from the South Dakota Board of Regents as well as South Dakota Science and Technology Authority private funding.
- This work was also supported in part under the US Department of Energy contract DE-AC02-05CH11231 and DE-SC0014223 and by National Science Foundation grant PHY-1506033.
- We gratefully acknowledge the logistical and technical support and the access to laboratory infrastructure provided to us by the Sanford Underground Research Facility







