



Copper Electroforming at Laboratorio Subterráneo de Canfranc (LSC)

S. Borjabad*, A. Ianni

Laboratorio Subterráneo de Canfranc (LSC), Spain

J.C. Amaré Tafalla

Universidad de Zaragoza, Spain

Outline

- LSC general presentation.
- CES (Copper Electroforming Service).
- Conclusions.

LSC General Presentation

External Buildings

EDIFICIO SEDE

- Headquarters & Administration
- Safety and Quality Assurance
- 23 offices
- 4 specialized laboratories
- Mechanical workshop
- Storage room
- Meeting room
- Library
- Conference & exhibition rooms
- 2 apartments



Surface: 1,821 m²
(2,115 m² built)




Surface: ~400 m²
(460 m² built)

CASA DE LOS ABETOS

- 2 Classroom
- 1 Conference room
- Exhibitions room

LSC General Presentation

Underground facilities



LAB2400

850 m rock overburden

2,450 meters of water equivalent (m.w.e.) depth

muon flux $\sim 4 \times 10^{-3} \text{ m}^{-2} \text{ s}^{-1}$



LSC General Presentation

Underground facilities

- ULBS (Ultra Low Background Service): 7 HPGe detectors, Hall C
- CRS (Clean Room Service): underground clean room class ISO 7 (ISO 6 in a sector)
- Radon abatement system (220 m³/ h, for NEXT, BiPo and ANAIS experiments), Hall A
- Radon detector (1 mBq m⁻³, in progress, collaboration with G. Zuzel, Krakow), Hall A
- Mechanical workshop
- Offices



Clean Room



Radon abatement system



Mechanical workshop

LSC General Presentation

Underground facilities

Hall A



Picture by J. Quiñoa

LSC General Presentation

Current Science Program at LSC

PHYSICS

ANAIS: dark matter (NaI, annual modulation)

ArDM: dark matter (two-phase LAr TPC)

TREX: dark matter (HP Gas TPC)

NEXT: $0\nu 2\beta$ decay (Enriched ^{136}Xe gas TPC)

CROSS: $0\nu 2\beta$ decay (^{100}Mo bolometers)

BiPo: $0\nu 2\beta$ decay (ancillary to Super-NEMO)

SuperK-Gd: material screening of Gd salts for Super - Kamiokande

CLYC-N: screening of neutrons in underground

A-KWISP: force sensor for short-range interactions

GEOPHYSICS

Geogyn: geodynamics (underground & surface) at local/ global scale

ETSEC: seismic sensors in the ET framework (characterization of Newtonian background)

BIOLOGY

GOLLUM: life characterization deep underground

LSC General Presentation



ULBS (Ultra-Low Background Service)



7 HPGe p-type coaxial (2 kg),
mounted and taking data

Hall C – LAB2400

Environmental monitoring &
material screening




Shielding characteristics

- 5-10 cm Cu-OFHC
- 20 cm very low ^{210}Pb activity lead
- Methacrylate Rn box.
- Door
- N_2 from boil-off evaporation

LSC General Presentation

ULBS (Ultra-Low Background Service)

Typical background spectrum (GeOroel)




| Detector Name | Diameter [mm] | Height [mm] | Weight [g] | Rel. Eff. [%] | FWHM @ 1332 keV [keV] | Cryostat Mat. |
|---------------|---------------|-------------|------------|---------------|-----------------------|---------------|
| GeOroel | 81.4 | 81.7 | 2230 | 109.0 | 1.85 | Al |
| GeTobazo | 81.2 | 81.2 | 2185 | 110.0 | 2.07 | Al |
| GeAnayet | 81.0 | 81.1 | 2183 | 109.0 | 1.96 | Al |
| GeAspe | 81.0 | 81.2 | 2187 | 108.0 | 1.94 | Al |
| GeLatuca | 81.0 | 81.2 | 2187 | 108.0 | 1.86 | Al |
| Asterix | 79.0 | 79.0 | 2031 | 95.1 | 2.08 | Cu |
| Obelix | 79.0 | 79.0 | 2031 | 92.8 | 2.00 | Cu |

Integral 40 keV -> 2700 keV $\text{day}^{-1} \text{kg}^{-1} = 184$ counts

$^{238}\text{U}/^{214}\text{Bi}$ (609 KeV) = 2.66 counts $\text{day}^{-1} \text{kg}^{-1}$

$^{232}\text{Th}/^{208}\text{Tl}$ (583.2 Kev) = 0.57 counts $\text{day}^{-1} \text{kg}^{-1}$

A MC simulation program, GEBIC, was developed using Geant4. Code adapted to include specific characteristics of each detector.




CES (Copper Electroforming Service)

Technique and set-up

Electroforming is a method of producing pieces by the deposition of a metal onto a mold, which is subsequently removed.

- Fixed current density direct electroplating
- High-purity commercial chemicals & ultra-pure water
- Cu-OFHC (anodes) & stainless steel 316L (cathode)



2 set-ups operative
Chemistry Lab – External Building

Technical details published at AIP Conference Proceedings 897, LRT2006

CES (Copper Electroforming Service)

Electroformed copper part

Electroformed copper endcap

(81.35 mm internal diameter, 80 mm height, 2.5 mm thickness, 627.2 g).

Process parameters: current density (3 A dm^{-2}), mold turning at 1.68 rev s^{-1} rotation speed, changing its rotation direction (forward or reverse direction) every 10 min.

- 1st mechanization treatment (only edges, to remove the dog-bone effect)
- 2nd mechanization treatment (external surface)



Electroforming process time: 90 h 30 min

Cleaning protocol (nitric acid etching and citric acid passivation)

Stored underground after the preparation

CES (Copper Electroforming Service)

Gamma spectrometry measurement

I. Bandac (LSC)

Gamma spectrometry measurement performed using a HPGe detector (GeOroel, 2Kg Ge coaxial p-type, ~100 % relative efficiency) of the electroformed copper part at ULBS (LSC).


Due to the limited free space inside the sample cavity, the height of the electroformed copper part had to be reduced cutting the piece with a saw (75.4 mm and 577.8 g).

| Isotope | ²³⁴ Th | ^{234m} Pa | ²³⁵ U | ²²⁸ Ra | ²²⁸ Th | ²²⁶ Ra | ¹³⁷ Cs | ⁶⁰ Co | ⁵⁸ Co | ⁵⁷ Co | ⁵⁶ Co | ⁵⁴ Mn | ⁴⁰ K |
|-------------------------------|-------------------|--------------------|------------------|-------------------|-------------------|-------------------|-------------------|------------------|------------------|------------------|------------------|------------------|-----------------|
| Units (mBq kg ⁻¹) | < 11.2 | < 72 | < 5.6 | < 2.23 | < 1.36 | < 9.8 | < 0.86 | < 0.71 | < 0.4 | < 0.8 | < 0.43 | < 0.31 | < 6.93 |

All the limits are 95 % C.L.

Measuring time: 50.4 days

Piece over a Marinelli container, bottom part close to the Ge detector



CES (Copper Electroforming Service)

Inductively Coupled Plasma Mass Spectrometry assay

S. Nisi, M.L. Di Vacri (LNGS, Italy)


Inductively-Coupled Plasma Mass Spectrometry (ICP-MS) assay carried out to analyze the Th and U contamination at the surface and bulk in copper samples

Sample preparation

- Nitric acid etching *
- Chromatographic extraction resins
- Eluted from the columns by ammonium oxalate


* Surface assay: samples etched once, ~2 g copper measured

Bulk assay: samples etched two times more, ~1 g copper measured



| Sample | Description | Surface assay | | Bulk assay | |
|--------|---|---------------|---------|------------|---------|
| | | Th [ppt] | U [ppt] | Th [ppt] | U [ppt] |
| #1 | OFHC copper, raw material, 15g | 280 | 48 | 4.6 | ~1 |
| #2 | Electroformed copper obtained at CES, 12.3g | 49 | 22 | <1 | <1 |

The error is estimated to be about 10%.



CES (Copper Electroforming Service)


Inductively Coupled Plasma Mass Spectrometry assay

I. J. Arnquist and E. W. Hoppe (PNNL, Richland)

Inductively-Coupled Plasma Mass Spectrometry (ICP-MS) assay carried out to analyze the Th and U contamination at bulk in copper samples

Sample preparation

- Nitric acid etching
 - ❖ Sample #1 totally digested by etching
 - ❖ Sample #2 cut in three pieces, 1/3 of mass etched away, remaining material completed dissolved by etching
- Pre-concentration (maximizing the analytes Th & U) and anion exchange separation (minimizing matrix)



#1 Remaining OFHC copper sample (LNGS)



#2 New electroformed copper sample

| Sample | Description | Th [ppt] | +/- sd | U [ppt] | +/- sd |
|-----------|--|----------|--------|---------|--------|
| #1 | Remaining OFHC copper | 0.967 | 0.059 | 0.196 | 0.011 |
| #2_LSC_01 | Electroformed copper obtained at CES, three pieces | 0.0426 | 0.0019 | <0.0497 | - |
| #2_LSC_02 | | 0.0345 | 0.0037 | <0.0502 | - |
| #2_LSC_03 | | 0.0363 | 0.0050 | <0.0498 | - |

Triplicate measurements of the same sample is shown for each sample measurement as "Inst. +/- 1s".

CES (Copper Electroforming Service)

Gamma spectrometry – ICP MS comparison

| OFHC Copper | ICP-MS assay | | | | | |
|----------------|---|-----------------------|--------------------------------------|--------------------|---------------------------------|---------------|
| | LNGS surface [mBq kg ⁻¹] | LNGS surface [ppt] | LNGS bulk [mBq kg ⁻¹] | LNGS bulk [ppt] | PNNL [mBq kg ⁻¹] | PNNL [ppt] |
| U | 0.6049 | 49 | 0.01234 | .1 | 0.00242 | 0.196 |
| Th | 1.1382 | 280 | 0.01869 | 4.6 | 0.00393 | 0.967 |

| EF Copper | Gamma spectrometry HPGe | | ICP-MS assay | | | | | |
|--------------|--|----------------------|---|-----------------------|--------------------------------------|--------------------|---------------------------------|-------------------|
| | LSC GeOroel [mBq kg ⁻¹] | LSC GeOroel [ppt] | LNGS surface [mBq kg ⁻¹] | LNGS surface [ppt] | LNGS bulk [mBq kg ⁻¹] | LNGS bulk [ppt] | PNNL [mBq kg ⁻¹] | PNNL [ppt] |
| U | < 11.2 (²³⁴Th) | < 907.2 | 0.2716 | 22 | < 0.012 | <1 | < 0.000614 | <0.0498 |
| Th | < 2.23 (²²⁸Ra) | < 548.5 | 0.1992 | 49 | < 0.0406 | <1 | 0.000147 | 0.0363 |

1 Bq ²³⁸U/kg = 81x10⁻⁹ g/g (ppb)
 1 Bq ²³²Th/kg = 246x10⁻⁹ g/g (ppb)


CES (Copper Electroforming Service)

LNGS & LSC Collaboration

Electroformed copper cylinder using Cu-ETP (UNI 5649-71) bars from LNGS (81.35 mm diameter, 118 mm height, 2.3 mm thickness, 547.6 g).

Process parameters: current density (3 A dm^{-2}), mold turning at 1.68 rev s^{-1} rotation speed, changing its rotation direction (forward or reverse direction) every 10 min.


- Two mechanization treatments (only edges, to remove the dog-bone effect)
- None final surface mechanization treatment



Electroforming process time: 75 h

None cleaning protocol

Stored underground after the preparation



CES (Copper Electroforming Service)

LNGS & LSC Collaboration

S. Nisi, M.L. Di Vacri (LNGS, Italy)

Inductively-Coupled Plasma Mass Spectrometry (ICP-MS) assay carried out for a semi-quantitative analysis at bulk in copper samples

Sample preparation

- Cleaning protocol (5% citric acid)
- Nitric acid etching (two steps)
~3.6 – 3.8 g of sample measured from the second etching

Reference Standard solution 10 ppb (Li, Ce, Y, Tl) added to a portion of the sample solution to evaluate the instrumental response

Work in progress

| | Starting copper (Cu ETP from LNGS) | Electroformed copper obtained at LSC | Removal efficiency |
|----|---------------------------------------|---|-----------------------|
| | [ng g ⁻¹] | [ng g ⁻¹] | [%] |
| Fe | 13 x 10 ³ | < 3 x 10 ³ | > 76.9 |
| Co | 1.6 x 10 ³ | < 1 | > 99.9 |
| Ag | 1.0 x 10 ³ | 240 | 76.0 |
| Sn | 19 x 10 ³ | < 5 | > 99.9 |
| Sb | 1.9 x 10 ³ | < 5 | > 99.7 |
| Nd | < 5 | 130 | |
| Bi | 180 | < 5 | > 97.2 |
| Pb | 49 x 10 ³ | < 50 | > 99.9 |

The uncertainty of results is estimated to be about 30% of the given values.

"ICP-MS measurements of ultra-low level radioactivity in solid material and comparison with γ - spectrometry within the CUPID experiment" M.L. Di Vacri (ICRM-LLRMT meeting, 2016).

CES (Copper Electroforming Service)

Requests & Collaborations

From 2014 performed electroformed copper pieces: ANAIS, LNGS Collaboration...

- ANAIS Experiment: 28 electroformed copper parts for 14 PMT encapsulation.



EF copper endcap



NaI(Tl) module assembly in the LSC Clean Room



Current configuration of ANAIS experiment

(Pictures courtesy of ANAIS Collaboration)

- LNGS Collaboration (Italy): study of the copper purification by the electroforming technique.

Work in progress

- Jagiellonian Univ. Collaboration (Poland): study of the residual $^{210}\text{Pb}/^{210}\text{Po}$ bulk content, surface radiopurity and searches for appropriate surface cleaning protocols of electroformed copper.

Work in progress

Conclusions

- The CES facilities allow to carry out R&D activities and give support to experiments working at LSC.
- Current cleaning protocol is not sufficient to clean surface contamination from the electroformed copper pieces.
- The comparison ICP MS - gamma spectrometric measurements demonstrates that the techniques are in agreement and complementary.
- The electroforming process performed at LSC resulted to be efficient for copper purification for several elements of interest.
- CES is being used to carry out several R&D activities in collaboration with other Laboratories and research.

Thank you!

