

INPC 2025

May 25-30, 2025
DCC, Daejeon, Korea



FRIB

FRIB First Three Years of User Operations and Performance Ramp Up

Sang-hoon Kim, FRIB/MSU
On behalf of FRIB Team

The 29th International Nuclear Physics Conference (INPC 2025)

May 26, 2025



MICHIGAN STATE
UNIVERSITY



U.S. DEPARTMENT
of **ENERGY** | Office of
Science

This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of Nuclear Physics and used resources of the Facility for Rare Isotope Beams (FRIB) Operations, which is a DOE Office of Science User Facility under Award Number DE-SC0023633.

Outline



- FRIB facility and operational status
- Superconducting linac operations and maintenance
- Target and beam dump operations and power ramp-up plan
- FRIB400 energy upgrade plan
- Summary



FRIB for Rare Isotope Science

- The world's largest heavy ion SC linac accelerating uranium beam up to 200 MeV/u with an ultimate beam power of 400 kW
- Separation of isotopes in-flight provides
 - Fast development time for any isotope
 - Beams of all elements and short half-lives
 - Fast, stopped, and reaccelerated beams


FRIB located in Michigan State University campus



1963	• Cyclotron Lab Established
1982	• First superconducting Cyclotron K500
Jun 2009	• DOE and MSU signed cooperative agreement
Sep 2010	• CD-1: Preferred alternatives decided
Aug 2013	• CD-2/3a: Project baselined and Civil construction started
Aug 2014	• Start of technical Construction
May 2021	• Linac construction complete
Jan 2022	• Project technical construction complete
Apr 2022	• CD-4
May 2022	• Start of User Operations




Facility Overview




- FRIB contains unique/original accelerator devices/systems such as:
 - the world's largest low- β superconducting linac,
 - liquid-lithium charge stripper.
- Facility upgrades are in-progress/planned:
 - High-Rigidity Spectrometer (in progress),
 - FRIB400 Linac Energy Upgrade (planned).

Demonstrated Acceleration of 200 MeV/u Uranium Beam

- $^{238}\text{U}^{78+}$ beam was accelerated to 200 MeV/u
 - Additionally, $^{36}\text{Ar}^{18+}$ beam was accelerated up to 300 MeV/u
- 323 out of 324 Linac SRF cavities have been used since FY2023 operation, which were also used for this beam acceleration



Beam Power Ramp-up in Parallel with User Operations



- Conducting user operations and, at the same time, beam power ramp-up (current ramp-up)
 - Currently operating at 20 kW, including uranium beam
 - Approach: phased beam power ramp-up with upgrades of beam intercepting devices such as target and beam dump as well as linac charge selector


User Operations with High Availability

- Total 6081 Scheduled Operating Beam Hours at 95.7% Availability for FY2024

- 4242 hours scheduled for FRIB experiments,
- 1839 hours for FSEE experiments (FRIB Single-Event Effect using Linac Segment 1)


- FSEE experiments scheduled in between FRIB experiments

- To meet FRIB users' needs for various isotope beams, which requires changes of target/wedge




Rare Isotope Production Optimized for User Experiments Requires Frequent Changes of Primary Beams

- Primary beam (isotope and energy), production target, and configuration of the fragment separator need to be optimized for each experiment
 - Changes of target and wedge degrader require replacement of physical devices in hot-cell via remote handling
- Primary beam in the linac also needs to be frequently changed to meet users' need
 - **Stable and reliable SC linac operation** and **high-level beam dynamics tools** are essential for efficient primary beam switching



Primary Beam Statistics Oct 2022 – Apr 2024




143 primary beam changes, including energy changes


Linac Beam Tuning and SRF Cavity Operation For Efficient User Operations

- Linac phasing and Instant Phase Setting for different m/q beams

Linac phasing example
(220 cavities during ARR05 commissioning)




Envelope matching using Instant Phase Setting
(model-based cavity field changes for a different beam)



(Courtesy of P. Ostroumov, A. Plastun)

- SRF cavity operation for nearly instant switch between different m/q beams

LS1 cavity field switching for various beams*
(104 cavities for FSEE experiments)




* via dynamic load compensation by cryomodule internal heaters such that the net heat load remained almost constant in each module



Simultaneous Acceleration of Multiple-Charge-State Beam


- Multiple-charge-state acceleration: key feature of the FRIB design to obtain the ultimate heavy ion beam current, such as uranium, at the target under the given limitation from the source
- Also helpful to reduce beam losses (heat loads) in the linac FS1 charge selector

Charge State Distribution
17 MeV/u ^{238}U
(Measurement)



Ion	E [MeV/u]	Stripping Efficiency Multi / 1q
$^{48}\text{Ca}^{19+,20+}$	225	97% / 71%
$^{64}\text{Zn}^{28+,29+}$	240	88% / 70%
$^{82}\text{Se}^{32+,33+}$	200	88% / 71%
$^{124}\text{Xe}^{48+,49+,50+}$	228	76% / 30%
$^{238}\text{U}^{73+ \sim 77+}$	177	83% / 21%



$^{238}\text{U}^{5q}$ beam envelope (simulation)



(Courtesy of T. Maruta)



Superconducting Linac with 324 Low-beta Coaxial SRF Cavities in 46 Cryomodules



	$\beta=0.041$ QWR	$\beta=0.085$ QWR	$\beta=0.29$ HWR	$\beta=0.53$ HWR
f_0 (MHz)	80.5	80.5	322	322
V_{acc} (MV)	0.81	1.8	2.1	3.7
E_{acc} (MV/m)	5.1	5.6	7.7	7.4
E_{pk} (MV/m)	31	33	33.3	26.5
B_{pk} (mT)	55	69	59.6	63.2

Quarter Wave Cryomodule				
β	Type	Component Counts (baseline + spares)		
		Cryomodules	Cavities	Solenoids
0.041	accelerating	3 + 1	12 + 4	6 + 2
	matching	1 + 1	4 + 4	-
0.085	accelerating	11 + 1	88 + 8	33 + 3
	matching	1 + 1	4 + 4	-
Half Wave Cryomodule				
0.29	accelerating	12	72	12
	accelerating	18	144	18
0.53	matching	1	4	-
TOTALS		46 + 3	324 + 16	69 + 5


Michigan State University
USA

Linac Cryomodule Operational Experience

- 80.5 MHz quarter-wave resonators (QWRs; 104 cavities, $\beta=0.041, 0.085$)
 - 4K operation is also stable with no microphonics issues

Typical phase lock stability performance of LS1 at 4K:


(Max P_{fwd} sampled every $\sim 1/4$ second and plotted for 7 hour duration)



- 322 MHz half-wave resonators (HWRs; 224 cavities, $\beta=0.23, 0.53$)
 - No issues/challenges associated with cavity and coupler multipacting during commissioning and operation: choice of HWR, FPC bias tee

$\beta=0.53$ HWR multipacting (MP)

Conditioning in CW mode: typically within 0.5-1 hour



Cryomodule Maintenance Program for Long-term Operation: Spare Cryomodules and In-situ Plasma Processing

- Strategy to address field emission degradation during long-term operation (first-ever experience in high-power heavy ion SC linac): spare cryomodules and in-situ plasma processing


First cryomodule replacement in linac tunnel (2024 summer)

Two adjacent CMs kept cold







Old CM

A warm diagnostics box temporarily removed during CM swap




New CM

QWR cryomodule plasma processing (PP) (first time in-situ PP in low-beta cryomodules)




SRF Development for Higher Q0/Gradient Spare Cryomodules

80.5 MHz $\beta=0.085$ QWR 4.3 K Q curves



322 MHz $\beta=0.53$ HWR 2.0 K Q curves





- Buffer Chemical Polishing (BCP) + 120 deg.C low-temperature baking (LTB) is superior to BCP-only for 4K operation
- **BCP + furnace LTB (120°C for 48 hours)** is a recipe for spare cavities

- Observed improvement of high-field Q-slope in electropolishing (EP) and EP + LTB, compared to BCP
- **EP or EP + LTB** is a recipe for spare cavities





High-power Beam Intercepting Devices: Linac Charge Stripper, Isotope Production Target and Beam Dump


Liquid-lithium (linac) charge stripper



Single-slice rotational graphite target



Static “mini-channel” beam dump




(Courtesy of T. Kanemura, P. Ostroumov, J. Song)


Target and Beam Dump Plan for Power Ramp-up

- Phased deployment of high-power targetry devices is planned; the devices are under development based on operational experience with high-power heavy ion beams


Multi-slice rotational graphite target



Rotational water beam dump




Linac rotational graphite charge selector



FRIB400 Energy Upgrade

2023 NSAC Long Range Plan




- Will double FRIB's beam energy, 400 MeV/u for uranium beam, using 644 MHz $\beta=0.65$ 5-cell elliptical cavities
 - To expand the scientific impact by increasing the yield of many rare isotopes tenfold
- Highlighted in the 2023 Long Range Plan for Nuclear Science (2023 LRP) as one of the strategic opportunities to advance discovery science of tomorrow
- FRIB's approach for future FRIB400
 - Developing two-cavity cryomodule as a spare buncher of the existing linac
 - Performing R&D for high Q_0 recipes, plasma processing
 - The linac energy upgrade project has not started yet

FRIB400 White Paper (2018)




5-cavity FRIB400 accelerating cryomodule




Parameter	Quantity
Number of Cryomodules	11
Cavity Per Cryomodule	5
Total Cavities	55

2-cavity S65 buncher cryomodule (FS2 buncher spare)




Technical Roadmap for Development of FRIB400 Cryomodule



Cavity design and fabrication

- Unjacketed 5-cell cavity vertical test: Achieved $Q_0 = 3.5 \times 10^{10}$ @ 17.5 MV/m
- Validated unjacketed cavity design
- Built a jacketed cavity



Tuner and coupler design and fabrication

- Built a tuner and performed room-temperature test
- Built fundamental power couplers (FPC) and performed low-power RF test

Surface preparations optimization

- Optimize High-pressure rinsing (HPR), clean assembly, other surface cleaning methods for field-emission-free performance

Jacketed cavity vertical test

- Validate jacketed cavity design together with surface preparation process


Integration test in Test Cryomodule

Goal: $Q_0 > 2e10$ @ 17.5 MV/m, $Q_L = 2 \times 10^7$, Max 15 kW CW


- Validate all subsystems design

Advanced SRF R&D

- Develop alternative high Q0 recipes
- Develop plasma processing method
- Study potential RF instability and develop mitigation methods
- Develop field emission mapping systems



1-cell HPR




Jacketed cavity




Test Cryomodule



S65 buncher cryomodule



FRIB400 accelerating cryomodule



Summary

- FRIB has been conducting user operations since May 2022, providing rare isotope beams to nuclear physics experiment users more than ~4000 hours per year, with a high reliability (>95%)
- Currently operating with a beam power of 20 kW. Plan to ramp up the beam power with phased deployment of higher-power beam intercepting devices such as target, beam dump, linac charge selector
- Maintenance program to keep such a high reliability is in place. In case of superconducting linac, we are building spare cryomodels with higher performance, and developing in-situ plasma processing to address field emission degradation in future long-term operation
- Additionally, FRIB400 energy upgrade, doubling the linac beam energy with new medium-velocity elliptical cavity cryomodels, is planned. Currently conducting SRF development for cavities, subsystems, and cryomodels

